

Project name:

Location:


Item: Qty:

Model:

Ideally suited for smoothie and ice-cream shops, small spaces, counter-top bars, mobile carts, food courts, lounges, boats, caterers, dental offices, day-care operators, guest houses, room service, espresso bars, kiosks, laboratories and much more!



# MULTI-PURPOSE COUNTER-TOP WAREWASHER





## ... or as a Glasswasher

Accessory No. 30132, 9-place insert for glass ware Note: Optional accessory No. 30133, 16-place insert for glass ware



## ... or as a Dishwasher

Accessory No. 30037, 6-place insert for plates up to 10 1/2" in diameter



## ... or for blender containers

Accessory No. 30131, 4-place insert









## PERFORMANCE FEATURES

- Completely automatic wash and rinse cycles including one wash program at 150°F. (65°C.) and one rinse program at 185°F. (85°C.)
- Hourly production: 20 racks of various items OR depending on rack insert used, the following quantities can be washed and rinsed:
  - 4-place insert for Blender Containers 80 / hr.
  - 9-place insert for Glassware 180 / hr.
  - 16-place insert for Glassware 320 / hr.
  - 6-place insert for Dishes 120 / hr.
- Built-in automatic detergent pump for consistent results each time
- Built-in automatic rinse-additive pump for sparkling final results

## **CONSTRUCTION FEATURES**

- Body, external housing, wash tank, and all chassis components in brushed stainless steel 304 18/10
- Constructed of insulated double-walled panels for low heat and noise emissions
- Unique and compact size for easy placement on a counter top, stand or mobile cart
- Door opening is designed to accept items up to a maximum height of 11"
- Integrated stainless steel booster with insulated lining
- Full width interior scrap screens of durable stainless steel
- · Internal screen for protection of motor-pump
- Safety micro-switch on the door to interrupt wash pump action
- Lower revolving wash and rinse arm with lateral upper fixed rinse arms built of fiberglass designed for maximum results and ease of maintenance
- Independently-operated heating elements alternating between the booster and wash tank
- Both alternating heating elements serve to reduce overall energy costs by lowering amperage consumption
- Thermostatic regulated control of both wash and rinse water
- Automatic fill and water level regulation of the wash tank
- Individual digital gauges for both wash and rinse temperatures
- Vertical integrated control panel for simple access and technical maintenance



#### MVP GROUP CORP.

5659 Royalmount Ave., Montreal, Qc, Canada H4P 2P9 TEL: (514) 737-9701 - TOLL FREE: (888) 275-4538 FAX: (514) 342-3854 - TOLL FREE FAX: (877) 453-8832

#### www.mvpgroupcorp.com - sales@mvpgroupcorp.com

**JET-TECH** is a registered trade mark of MVP Group. Specifications subject to change without notice.

# TECHNICAL FEATURES

- Rack capacity: 13.75" x 13.75"" (350 mm x 350 mm)
- Complete operating cycle: 165 seconds wash and 15 seconds rinse
- Wash tank capacity: 2.1 U.S. gallons (8 litres)
- Wash tank element: 1400 watts (1.4 Kw)
- Wash temperature: 150°F (65°C)
- Booster capacity: 0.53 U.S. gallons (2.0 litres)
- Booster element: 1400 watts (1.4 Kw)
- Rinse (water) temperature: 185°F (85°C)
- Maximum power absorption: 1500 watts (1.5 Kw)
- Wash motor-pump: 100 watts
- Power supply: 110 Volt / 60 Hz


(power cord with NEMA 5-20 plug included)


- Optional: 220 Volt / 50 Hz Special Order (power cord and plug included)
- Amperage: Single phase 13.5A
- Water consumption: 0.5 U.S. gallons per cycle (2.9 litres)
- Recommended pressure: 30 p.s.i. (dynamic)
- Water inlet connection: 3/4" male garden hose fitting (hose included)
- Drain connection: 1" ID hose connection (hose included)
- Shipping weight: 72 lbs (32.8 kg)


## **ACCESSORIES**

## F-14 supplied with:

- (1) open rack 13.75" x 13.75" (350 mm. X 350 mm.)
- (1) 4-place insert #30131 for blender containers
- (1) 9-place insert #30132 for glassware
- (1) 6-place insert #30037 for plates up to 10.5" diameter
- (1) 15-place insert #30035 for saucers and/or small plates
- (1) cutlery holder #30026
- Optional: •16-place insert #30133 for glassware
  - Drain water tempering kit
  - Pressure reducing valve (PRV) kit







Warranty: 90 days on labor and 1 year on parts. Certain conditions apply. See Owner's Manual for details.