

REACH-IN TOP-MOUNT SERIES REFRIGERATORS

Features

- CFC free refrigerant and foam insulation
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- 3 adjustable, heavy-duty epoxy coated wire shelves per door
- Condensate heating element built into condensate pan for efficient evaporation of excess water
- Easy to mount 4" casters (lockable in front) are standard with all units
- Locking doors on all units. IT28R door swing is field reversible
- Self-closing doors that remain open at 90 degrees
- Magnetic gasket can be replaced without any tools
- Exterior: 430 stainless steel
- Interior: 304 stainless steel
- R-290 Natural refrigerant
- Temperature: 33 to 40°F / 0.5 to 4°C
- Electrical: 115/60/1 with NEMA 5-15P plug, 10ft cord



NEMA
5-15P



IT28R*



IT56R*



IT82R

Specifications

DESIGNED TO OPERATE IN AMBIENT TEMPERATURES BETWEEN 40F-90F FOR OPTIMUM PERFORMANCE.




Model	Doors	Ext. Dimensions W X D X H (In)	Int.. Dimensions W X D X H (In)	Amps	H.P	Ship Weight
IT28R*	1	26.8 X 32.7 X 82.3	22.2 X 27.6 X 59.1	3	1/5	307 lbs
IT56R*	2	53.9 X 32.7 X 82.3	49.4 X 27.6 X 59.1	4.5	1/4	490 lbs
IT82R	3	81.0 X 32.7 X 82.3	76.4 X 27.6 X 59.1	7	1/2	598 lbs

REACH-IN TOP-MOUNT SERIES REFRIGERATORS




Dimensions in inches (mm)

IT28R*



IT56R*



IT82R

