

REACH-IN BOTTOM-MOUNT SERIES REFRIGERATORS GLASS DOORS

Features

- CFC free refrigerant and foam insulation
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- 4 adjustable, heavy-duty epoxy coated wire shelves per door
- Clip-on shelf tag holders
- Condensate heating element built into condensate pan for efficient evaporation of excess water
- Easy to mount 4" casters (lockable in front) are standard with all units
- Self-closing doors that remain open at 90 degrees
- Magnetic gasket can be replaced without any tools
- Exterior: 430 stainless steel
- Interior: 304 stainless steel
- R-290 Natural refrigerant
- Temperature: 33 to 40°F / 0.5 to 4°C
- Electrical: 115/60/1 with NEMA 5-15P plug, 10ft cord







IB54RG

Specifications

DESIGNED TO OPERATE IN AMBIENT TEMPERATURES BETWEEN 40F-90F FOR OPTIMUM PERFORMANCE.





Model	Doors	Ext. Dimensions W X D X H (In)	Int Dimensions W X D X H (In)	Amps	H.P	Ship Weight
IB27RG	1	26.8 X 31.9 X 82.3	22.2 X 27.6 X 50.2	3	1/5	366 lbs
IB54RG	2	53.9 X 31.9 X 82.3	49.4 X 27.6 X 50.2	4.5	1/4	598 lbs





REACH-IN BOTTOM-MOUNT SERIES REFRIGERATORS GLASS DOORS





Dimensions in inches (mm)

31.9(810) 25(635) 2.0(50) 2.4(60) ---2.4(60) 50.2(1276) 53.7(1365) 76.8(1950) 82.3(2090) 26.8(680) 1.2(30) 31.9(810) 27.6(700) 22.2(564) 2.4(60) 2.4(60) (G) S 5.5(140)

IB54RG

IB27RG

